

# PIPE CLAMPS

## SK Series




Fig. 1




Fig. 3




Fig. 2




Fig. 4

### One Piece Break Apart Clamp


Available in Electro-Galvanized (EG), 304 Stainless Steel (SS), Aluminum (AL) or Copper Plated (CP), sized for copper tubing

•Sized for Steel Pipe or Rigid and EMT Conduit

•Retained Bolt and built in nut (thread impression)\*



See chart for Static Load Limit



Ultimate Static Load Limit 75 LBS.



Ultimate Static Load Limit 50 LBS.

\*Aluminum SK's do not have thread impression. An aluminum bolt and nut are normally provided. Also available with standard steel nut and bolt.



Material	Part #	Fig. No.	SIZE	STATIC/LOAD LIMIT
ELECTRO GALVANIZED STEEL (EG)	SK85I	1	1/2	200
	SK125I	1	3/4	200
	SK165I	1	1"	200
	SK205I	1	1-1/4	200
	SK245I	1	1-1/2	200
	SK325I	1	2"	200
	SK405I	2	2-1/2	350
	SK485I	2	3"	350
	SK565I	2	3-1/2	350
ALUMINUM (AL)*	SK8AL	3	1/2	150
	SK12AL	3	3/4	150
	SK16AL	3	1"	150
	SK20AL	3	1-1/4	150
	SK24AL	3	1-1/2	150
	SK32AL	3	2"	150
	SK40AL	4	2-1/2	200
	SK48AL	4	3"	200
	SK56AL	4	3-1/2	200
STAINLESS STEEL (SS)	SK8SS	1	1/2	200
	SK12SS	1	3/4	200
	SK16SS	1	1"	200
	SK20SS	1	1-1/4	200
	SK24SS	1	1-1/2	200
	SK32SS	1	2"	200
	SK40SS	2	2-1/2	350
	SK48SS	2	3"	350
	SK56SS	2	3-1/2	350
COPPER PLATED STEEL (CP)	SKT8CP	1	1/2" (5/8)	200
	SKT12CP	1	3/4" (7/8)	200
	SKT16CP	1	1" (1-1/8)	200
	SKT20CP	1	1-1/4" (1-3/8)	200
	SKT24CP	1	1-1/2" (1-5/8)	200
	SKT32CP	1	2" (2-1/8)	200
	SKT40CP	2	2-1/2" (2-5/8)	350
	SKT48CP	2	3" (3-1/8)	350
	SKT56CP	2	3-1/2" (3-5/8)	350
SKT64CP	2	4" (4-1/8)	350	

## Clamps for Rigid Conduit


Part #	SIZE	O.D.	DESIGN LOAD
RIGD 3/8	3/8"	.675"	400
RIGD 1/2	1/2"	.840"	400
RIGD 3/4	3/4"	1.050"	600
RIGD 1	1"	1.315"	600
RIGD 1-1/4	1-1/4"	1.660"	600
RIGD 1-1/2	1-1/2"	1.900"	800
RIGD 2	2"	2.375"	800
RIGD 2-1/2	2-1/2"	2.875"	800
RIGD 3	3"	3.500"	800
RIGD 3-1/2	3-1/2"	4.000"	1000
RIGD 4	4"	4.500"	1000
RIGD 5	5"	5.563"	1000
RIGD 6	6"	6.625"	1000
RIGD 8	8"	8.625"	1000



## Clamps for EMT Conduit

Part #	SIZE	O.D.	DESIGN LOAD
EMTC 1/2	1/2"	.706"	400
EMTC 3/4	3/4"	.922"	600
EMTC 1	1"	1.163"	600
EMTC 1-1/4	1-1/4"	1.510"	600
EMTC 1-1/2	1-1/2"	1.740"	800
EMTC 2	2"	2.197"	800

## Clamps for Rigid or EMT Conduit



Part #	SIZE	DESIGN LOAD
UNIV 1/2	1/2"	400
UNIV 3/4	3/4"	600
UNIV 1	1"	600
UNIV 1-1/4	1-1/4"	600
UNIV 1-1/2	1-1/2"	800
UNIV 2	2"	800

Unless noted, Standard Finish: EG 11

# PIPE CLAMPS

## O.D. Clamp for Tubing

Part #	O.D.	DESIGN LOAD
O.D. 1/4	.250"	400
O.D. 3/8	.375"	400
O.D. 1/2	.500"	400
O.D. 5/8	.625"	400
O.D. 3/4	.750"	400
O.D. 7/8	.870"	400
O.D. 1	1.000"	600
O.D. 1-1/8	1.125"	600
O.D. 1-1/4	1.250"	600
O.D. 1-3/8	1.375"	600
O.D. 1-1/2	1.500"	600
O.D. 1-5/8	1.625"	600
O.D. 1-3/4	1.750"	800
O.D. 1-7/8	1.870"	800
O.D. 2	2.000"	800
O.D. 2-1/8	2.125"	800
O.D. 2-1/4	2.250"	800
O.D. 2-3/8	2.375"	800
O.D. 2-1/2	2.500"	800
O.D. 2-5/8	2.625"	800
O.D. 2-3/4	2.750"	800
O.D. 2-7/8	2.875"	800
O.D. 3	3.000"	800
O.D. 3-1/8	3.125"	800
O.D. 3-1/4	3.250"	800
O.D. 3-3/8	3.375"	800
O.D. 3-1/2	3.500"	1000
O.D. 3-5/8	3.625"	1000
O.D. 3-3/4	3.750"	1000
O.D. 3-7/8	3.875"	1000
O.D. 4	4.000"	1000
O.D. 4-1/8	4.125"	1000
O.D. 4-1/4	4.250"	1000
O.D. 4-3/8	4.375"	1000
O.D. 4-1/2	4.500"	1000
O.D. 4-5/8	4.625"	1000
O.D. 4-3/4	4.750"	1000
O.D. 4-7/8	4.875"	1000
O.D. 5	5.000"	1000
O.D. 5-1/8	5.125"	1000
O.D. 5-1/4	5.250"	1000
O.D. 5-3/8	5.375"	1000
O.D. 5-1/2	5.500"	1000
O.D. 5-5/8	5.625"	1000
O.D. 5-3/4	5.750"	1000
O.D. 5-7/8	5.875"	1000
O.D. 6	6.000"	1000
O.D. 6-1/8	6.125"	1000
O.D. 6-1/4	6.250"	1000
O.D. 6-3/8	6.375"	1000
O.D. 6-1/2	6.500"	1000
O.D. 6-5/8	6.625"	1000
O.D. 6-3/4	6.750"	1000
O.D. 6-7/8	6.875"	1000
O.D. 7	7.000"	1000
O.D. 7-1/8	7.125"	1000
O.D. 7-1/4	7.250"	1000
O.D. 7-3/8	7.375"	1000
O.D. 7-1/2	7.500"	1000
O.D. 7-5/8	7.625"	1000
O.D. 7-3/4	7.750"	1000
O.D. 7-7/8	7.875"	1000
O.D. 8	8.000"	1000
O.D. 8-1/8	8.125"	1000
O.D. 8-1/4	8.250"	1000
O.D. 8-3/8	8.375"	1000
O.D. 8-1/2	8.500"	1000
O.D. 8-5/8	8.625"	1000



## Clamps for Copper Tubing standard Copper Plated finish Sized for Copper Tubing


Part #	SIZE	O.D.	DESIGN LOAD
COPC 1/4	1/4"	.375"	400
COPC 3/8	3/8"	.500"	400
COPC 1/2	1/2"	.625"	400
COPC 3/4	3/4"	.875"	400
COPC 1	1"	1.125"	600
COPC 1-1/4	1-1/4"	1.375"	600
COPC 1-1/2	1-1/2"	1.625"	600
COPC 2	2"	2.125"	800
COPC 2-1/2	2-1/2"	2.625"	800
COPC 3	3"	3.125"	800
COPC 3-1/2	3-1/2"	3.625"	1000
COPC 4	4"	4.125"	1000
COPC 5	5"	5.125"	1000
COPC 6	6"	6.125"	1000

## Cushion Clamps for Pipe and Copper Tubing standard Yellow Chromate finish

- Inhibits Galvanic Corrosion
- Dampens Sound and Vibrations
- Service Temperature Range  
-50°F to +275°F

### Tube Cushion Clamps (sized by O.D.)

Part #	O.D.
TCC 1/4	.250"
TCC 3/8	.375"
TCC 1/2	.500"
TCC 5/8	.625"
TCC 3/4	.750"
TCC 7/8	.870"
TCC 1	1.000"
TCC 1-1/8	1.125"
TCC 1-1/4	1.250"
TCC 1-3/8	1.375"
TCC 1-1/2	1.500"
TCC 1-5/8	1.625"
TCC 1-3/4	1.750"
TCC 1-7/8	1.870"
TCC 2	2.000"
TCC 2-1/8	2.125"
TCC 2-1/4	2.250"
TCC 2-3/8	2.375"
TCC 2-5/8	2.625"
TCC 3-1/8	3.125"
TCC 3-5/8	3.625"
TCC 4-1/8	4.125"



### Pipe Cushion Clamps


Part #	SIZE	O.D.
PCC 3/8	3/8"	.675"
PCC 1/2	1/2"	.840"
PCC 3/4	3/4"	1.060"
PCC 1	1"	1.315"
PCC 1-1/4	1-1/4"	1.660"
PCC 1-1/2	1-1/2"	1.900"
PCC 2	2"	2.375"
PCC 2-1/2	2-1/2"	2.875"
PCC 3	3"	3.500"
PCC 3-1/2	3-1/2"	4.000"
PCC 4	4"	4.500"
PCC 5	5"	5.583"
PCC 6	6"	6.825"

# PIPE CLAMPS

## Vibra Strip, Pipe Cushion

Isolation material for use with pipe clamps

- Inhibits Galvanic Corrosion
- Dampens Sound and Vibrati
- Service Temperature Range  
-75°F to +375°F



A sizing chart is provided on every box.

Vibra Strip is designed for use with refrigeration lines, HVAC, copper tubing, glass pipe and hydraulic lines. It provides an energy-absorption barrier between the lines and the mounting material, also allowing for expansion and contraction within the mounting system.


## RA/PAR/ET Clamps

for attaching pipe or conduit to beams or angle iron

### Right Angle (RA) Pipe Support

Standard Finish: Hot Dip Galvanized  
(U-Bolt and 2 nuts included)

Size 3/8" thru 4" Pipe



(maximum 3/4" flange thickness)

### Parallel (PAR) Pipe Support

Standard Finish: Hot Dip Galvanized  
(Bolt and Nut included)

Size 3/8" thru 4" Pipe



(maximum 3/4" flange thickness)

### Edge Type (ET) Pipe Support

Standard Finish: Hot Dip Galvanized  
(Bolt and Nut included)

Size 3/8" thru 4" Pipe



(maximum 3/4" flange thickness)


## EPS One Hole EMT Strap

for Thin Wall Conduit




Part #	Conduit Size	W	Hole Size
EPS 1/2	1/2"	3/4"	9/32"
EPS 3/4	3/4"	7/8"	9/32"
EPS 1	1"	1"	9/32"
EPS 1-1/4	1-1/4"	1-1/4"	9/32"
EPS 1-1/2	1-1/2"	1"	11/32"
EPS 2	2"	1-1/4"	11/32"

## STR One Hole Pipe Strap



Part #	O.D. Size	B	Hole Size
STR 1/4	1/4"	7/8"	9/32"
STR 5/16	5/16"	15/16"	9/32"
STR 3/8	3/8"	31/32"	9/32"
STR 1/2	1/2"	1-1/32"	9/32"
STR 5/8	5/8"	1-3/32"	9/32"
STR 3/4	3/4"	1-5/32"	9/32"
STR 7/8	7/8"	1-7/32"	9/32"
STR 1	1"	1-9/32"	9/32"

## 2STR Two Hole Pipe Strap



Part #	Pipe Size	A	B	Hole Size	Design Load
2STR 1/2	1/2"	3-3/32"	1-17/32"	9/32"	600
2STR 3/4	3/4"	5-5/16"	1-21/32"	9/32"	600
2STR 1	1"	7-11/16"	1-27/32"	9/32"	600
2STR 1-1/4	1-1/4"	9-29/32"	1-31/32"	9/32"	600
2STR 1-1/2	1-1/2"	11-5/8"	2-3/32"	9/32"	600
2STR 2	2"	13-7/8"	2-15/16"	7/16"	1200
2STR 2-1/2	2-1/2"	16-1/8"	3-1/16"	7/16"	1200
2STR 3	3"	18-7/8"	3-7/16"	7/16"	1200
2STR 3-1/2	3-1/2"	21-7/8"	3-15/16"	7/16"	1200
2STR 4	4"	24"	4"	7/16"	1500
2STR 5	5"	28-13/16"	4-13/16"	7/16"	1500
2STR 6	6"	32-7/8"	4-15/16"	7/16"	1500
2STR 8	8"	41-15/16"	5-31/32"	7/16"	1500

Unless noted, Standard Finish: EG